GEOTEXTILE FABRIC

APPROVED FLEXIBLE PLASTIC GASKET MATERIAL

APPROVED FLEXIBLE PLASTIC GASKET MATERIAL


FOR PIPES LESS THAN OR EQUAL TO 36" ROUND OR EQUIVALENT ARCH

FOR PIPES GREATER THAN 36" ROUND OR EQUIVALENT ARCH AND FOR ALL SIZES OF 6 X I AND 5 X I CORRUGATIONS


#### METHOD OF SEALING ANNULAR JOINT AT CONNECTING BAND WHERE TWO PIPE SECTIONS ARE JOINED


#### FLEXIBLE PLASTIC GASKET SYSTEM

T2 & T3 JOINTS AS SHOWN (WITH RODS & LUGS).
TI JOINT SIMILAR, EXCEPT REQUIRES ONLY ONE STRIP
OF PLASTIC GASKET MATERIAL IN SECOND CORRUGATION
EACH SIDE OF JOINT.




CONNECTION DETAIL
DOUBLE HARNESS






\*BAND LAP SEALANT TO BE FLEXIBLE PLASTIC GASKET MATERIAL. REQUIRED THICKNESS IN TABLE. REQUIRED WIDTH IS BAND WIDTH PLUS 2".

# CONNECTION DETAIL DOUBLE HARNESS





## CONNECTING BAND WITH ROD & LUG

# TWO PIECE BAND FLEXIBLE PLASTIC GASKET MATERIAL TO" MIN. LAP GEOTEXTILE FABRIC

# (FLEXIBLE PLASTIC GASKET SYSTEM)

# ALTERNATE CONNECTING BANDS O-RING SYSTEM

GEOTEXTILE FABRIC CLOTH REQUIRED - SAME AS SHOWN ABOVE.


# O-RING AND FLEXIBLE GASKET THICKNESS PIPE SIZE CORRUGATION O-RING THICKNESS 36" & UNDER 1/2" LARGER THAN 36" 1" ALL SIZES 1" 13/6" 1" 13/8" 11/2"

#### GENERAL NOTES:

- 1) O-RING GASKETS WILL BE REQUIRED WHENEVER O-RING SYSTEM CONNECTING BANDS ARE USED. O-RING GASKETS SHALL BE IDENTIFIED BY SIZE, DIAMETER, BATCH OR REEL NUMBER AND PLANT.
- 2) HELICAL ENDS SHALL BE RE-ROLLED AS PER CURRENT LA DOTD STANDARD SPECIFICATIONS.
- 3) FOR O-RING JOINT SYSTEMS, BOLTS SHALL BE TORQUED TO A MINIMUM OF 40 FT.LBS.
- 4) FOR FLEXIBLE PLASTIC GASKET SYSTEM ROUND PIPE, A MINIMUM OF 4 GALVANIZED 1/2" DIAMETER STEEL RODS AND LUGS SHALL BE PLACED OVER THE CONNECTING BAND. RODS MAY BE 2 PIECE FOR PIPE LARGER THAN 48".
- 5) GEOTEXTILE FABRIC SHALL CONFORM TO CURRENT LA DOTD STANDARD SPECIFICATIONS.
- 6) ARCH PIPE SHALL USE THE FLEXIBLE PLASTIC GASKET SYSTEM WITH APPROVED ANGLES OR STRAPS.
- 7) ALL GASKET MATERIAL SHALL BE APPROVED PRODUCTS ON CURRENT LA DOTD QUALIFIED PRODUCTS LIST.
- 8) PIPE JOINTS TO BE IN ACCORDANCE WITH CURRENT LA DOTD STANDARD SPECIFICATIONS.

### METHOD OF SEALING LONGITUDINAL JOINTS AT TWO PIECE CONNECTING BAND

(FLEXIBLE PLASTIC GASKET SYSTEM)



\GangO29\dgn\stdplans\2sam- I.dgn